

ギヤカップリング外形寸法図






表2 BZ形ギヤカップリング寸法表 (mm)

減速比	kW										ユサ ニ イ ツ ズ	A	B	C	D	E	F	G	J	K	L	LA	M	N	O	d	p	dH	pH	キーミゾ					重量	
	高 速 軸 回 転 数 rpm																													低速軸		高速軸				
	1800	1500	1200	1000	900	750	600	500	400	300																				α	β	Q	βH	QH		(kg)
1/5	0.41	0.37	0.32	0.28	0.26	0.22	0.19	0.16	0.14	0.11	B 7	325	260	225	110	220	85	20	55	60	70	50	260	160	w 3/8	25	47	16	35	7	4	44	5	3	32	34
	0.82	0.75	0.65	0.57	0.52	0.45	0.37	0.32	0.28	0.22	B 9	350	270	250	125	220	100	25	65	65	80	55	290	180	w 1/2	30	55	18	35	7	4	52	5	3	32	41
	1.6	1.5	1.3	1.2	1.1	0.9	0.75	0.65	0.55	0.45	B 10	385	290	285	140	240	110	25	65	70	80	55	325	205	w 1/2	35	55	22	47	10	4.5	52	7	4	44	53
	2.4	2.2	1.9	1.6	1.5	1.3	1	0.9	0.75	0.6	B 12	440	330	340	170	270	130	32	80	85	105	75	400	240	w 3/4	45	72	25	47	12	4.5	68	7	4	44	80
	4.1	3.7	3.2	2.8	2.6	2.2	1.9	1.6	1.4	1.1	B 13	480	350	340	170	290	130	32	80	85	115	85	400	260	w 3/4	50	82	28	55	12	4.5	78	7	4	52	90
をこえ1/5	6.1	5.5	4.8	4.1	3.7	3.2	2.6	2.2	1.9	1.5	B 14	515	390	410	200	320	160	40	90	95	120	85	460	290	w 3/4	55	82	32	55	15	5	78	10	4.5	52	140
	8.2	7.5	6.5	5.7	5.2	4.5	3.7	3.2	2.8	2.2	B 15	560	420	410	200	350	160	40	95	95	135	100	460	310	w 3/4	60	97	35	55	15	5	94	10	4.5	52	170
	12.2	11	9.5	8.2	7.5	6.5	5.2	4.5	3.7	3	B 16	625	450	430	220	380	170	40	100	95	155	120	500	355	w 3/4	70	112	40	72	18	6	108	10	4.5	68	210
	16.5	15	13	11.5	10.5	9	7.5	6.5	5.5	4.5	B 18	680	500	485	240	420	190	45	110	110	165	125	545	380	w 3/4	80	122	45	72	20	7	118	12	4.5	68	280
	24.5	22	19	16.5	15	13	10.5	9	7.5	6	B 21	755	540	510	260	460	200	45	115	115	185	145	580	415	w 3/4	90	142	50	82	24	8	138	12	4.5	78	350
1/15	33	30	26	23	21	18	15	13	11	9	B 22	815	600	580	280	510	230	50	125	125	190	145	635	450	w 1	100	142	55	82	28	9	138	15	5	78	460
	41	38	34	30	27	23	19	16.5	14	12	B 23	950	640	600	300	550	240	50	130	125	215	170	670	480	w 1	105	162	60	97	28	9	155	15	5	92	550
	51	47	42	37	34	29	24	21	18	15	B 25	1015	690	690	330	600	280	55	140	130	215	170	745	500	w 1	110	162	65	97	28	9	155	18	6	92	700
	0.41	0.37	0.32	0.28	0.26	0.22	0.19	0.16	0.14	0.11	B 8	340	270	260	125	220	100	25	65	65	80	55	290	180	w 1/2	30	55	16	35	7	4	52	5	3	32	40
	0.82	0.75	0.65	0.57	0.52	0.45	0.37	0.32	0.28	0.22	B 10	360	290	285	140	240	110	25	65	70	80	55	325	205	w 1/2	35	55	18	35	10	4.5	52	5	3	32	51
1/5	1.6	1.5	1.3	1.2	1.1	0.9	0.75	0.65	0.55	0.45	B 12	425	330	340	170	270	130	32	80	85	105	75	400	240	w 3/4	45	72	22	47	12	4.5	68	7	4	44	66
	2.4	2.2	1.9	1.6	1.5	1.3	1	0.9	0.75	0.6	B 13	465	350	340	170	290	130	32	80	85	115	85	400	260	w 3/4	50	82	25	47	12	4.5	78	7	4	44	90
	4.1	3.7	3.2	2.8	2.6	2.2	1.9	1.6	1.4	1.1	B 14	505	390	410	200	320	160	40	90	95	120	85	460	290	w 3/4	55	82	28	55	15	5	78	7	4	52	135
	6.1	5.5	4.8	4.1	3.7	3.2	2.6	2.2	1.9	1.5	B 15	550	420	410	200	350	160	40	95	95	135	100	460	310	w 3/4	60	97	32	55	15	5	94	10	4.5	52	170
	8.2	7.5	6.5	5.7	5.2	4.5	3.7	3.2	2.8	2.2	B 16	600	450	430	220	380	170	40	100	95	155	120	500	355	w 3/4	70	112	35	55	18	6	108	10	4.5	52	205
をこえ1/15	12.2	11	9.5	8.2	7.5	6.5	5.2	4.5	3.7	3	B 19	670	500	485	240	420	190	45	110	110	165	125	545	380	w 3/4	80	122	40	72	18	6	108	10	4.5	68	280
	16.5	15	13	11.5	10.5	9	7.5	6.5	5.5	4.5	B 21	725	540	510	260	460	200	45	115	115	185	145	580	415	w 3/4	90	142	45	72	24	8	138	12	4.5	68	340
	24.5	22	19	16.5	15	13	10.5	9	7.5	6	B 22	795	600	580	280	510	230	50	125	125	190	145	635	450	w 1	100	142	50	82	28	9	138	15	5	78	450
	33	30	26	23	21	18	15	13	11	9	B 24	880	650	620	300	560	250	50	130	125	210	165	680	490	w 1	110	162	55	82	28	9	155	15	5	78	570
	41	38	34	30	27	23	19	16.5	14	12	B 26	1065	750	700	340	650	280	60	150	145	245	195	750	540	w 1 1/2	120	187	60	97	32	10	180	15	5	92	820
1/30	51	47	42	37	34	29	24	21	18	15	B 28	1120	780	700	350	680	280	60	150	145	250	200	795	570	w 1 1/2	130	187	65	97	35	11	180	18	6	92	920